

Dati tecnici Baxi Moonlight Mono Split

		9.000 Btu/h	12.000 Btu/h	18.000 Btu/h	24.000 Btu/h
Potenza frigorifera resa nominale (min-max)	kW	2,55 (1,00-3,30)	3,60 (1,20-3,80)	5,30 (1,90-5,50)	7,03 (2,90-7,30)
Potenza frigorifera assorbita nominale (min-max)	kW	0,78 (0,10-1,44)	1,10 (0,10-1,60)	1,65 (0,21-1,73)	2,20 (0,37-2,90)
SEER		6,5	6,2	6,5	6,4
Classe di efficienza in raffreddamento		 A++	 A++	 A++	 A++
Potenza termica resa nominale (min-max)	kW	2,65 (1,10-3,30)	3,70 (1,00-3,80)	5,40 (1,40-5,60)	7,05 (2,10-8,00)
Potenza termica assorbita nominale (min-max)	kW	0,72 (0,20-1,40)	1,02 (0,20-1,35)	1,50 (0,31-2,00)	1,96 (0,44-2,60)
SCOP		4,2	4,2	4,1	4,3
Classe di efficienza in riscaldamento		 A+	 A+	 A+	 A+
Unità esterna		LSGT25-S	LSGT35-S	LSGT50-S	LSGT70-S
Massima potenza assorbita	kW	1,50	1,90	2,90	3,70
Massima corrente assorbita	A	8,0	9,5	12,0	16,0
Alimentazione	V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50
Gas refrigerante (GWP)		R32 (675)	R32 (675)	R32 (675)	R32 (675)
Quantità gas refrigerante	kg	0,58	0,68	1,28	1,44
tCO2 equivalenti	t	0,39	0,46	0,86	0,97
Potenza sonora	dB(A)	60	58	62	64
Dimensioni (LxHxP)	mm	720x540x260	720x540x260	802x535x298	900x681x343
Peso	kg	27	27	35	45
Attacchi linea liquido	mm	6,35 (1/4")	6,35 (1/4")	6,35 (1/4")	6,35 (1/4")
Attacchi linea gas	mm	9,52 (3/8")	9,52 (3/8")	12,7 (1/2")	15,88 (5/8")
Massima lunghezza totale del circuito frigorifero	m	20	20	25	25
Dislivello massimo tra unità interna-esterna	m	10	10	15	15
Metri di precarica	m	7	7	7	7
Unità interna		LSGNW25	LSGNW35	LSGNW50	LSGNW70
Potenza sonora	dB(A)	53	53	58	59
Dimensioni (LxHxP)	mm	800x300x198	800x300x198	970x315x235	1100x330x235
Peso	kg	9	9	12,5	15
Attacchi linea liquido	mm	6,35 (1/4")	6,35 (1/4")	6,35 (1/4")	6,35 (1/4")
Attacchi linea gas	mm	9,52 (3/8")	9,52 (3/8")	12,7 (1/2")	15,88 (5/8")